



Interior Stain Formula

Technical Data Sheet

March 2013

IS-Series

TR-Series

ST-Series

SS-Series

Description

The Timber Pro Interior Stain Formula is a deeply penetrating natural oil wood stain specially formulated to enhance and beautify the color of your interior wood. The Interior Stain Formula provides a low VOC and a low odour staining alternative for your interior wood.

Where to Use

Interior Stain formula is a versatile wood stain providing a broad colour palette achieve the desired colors to match your interior décor.

Used in combination with Timber Pro Crystal urethane this provides a durable topcoat to protect your interior wood projects.

- All interior wood walls, doors
- All interior wood trim work
- Interior wood floors
- Interior wood cupboards and countertops

RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

Features and Benefits

- Broad Colour Range of 56 colours to match all your interior needs.
- Low odour making ideal for interior application.
- 3 Sheen levels: Used in combination with Timber Pro Crystal Urethane a satin, semi-gloss and gloss finish can be achieved to match and accent your interior decor
- Easy to apply with spray, nylon polyester brush, or paint pad
- Low VOC formula is better for the environment.
- Easy soap and water cleanup

Interior Stain Formula

Technical Data Sheet

March 2013

IS -Series

TR-Series

ST-Series

SS-Series

Color Range and Packaging

Color:	Clear (IS series)	Interior	10 colors
	(TR series)	Transparent	24 colors available
	(ST series)	Semi Transparent	18 colors available
	(SS series)	Semi Solid	14 colors available

Packaging: 1 US Quart, 1 US Gallon

Properties

Viscosity -	20-21 secs Zahn cup #2
Gloss Level -	55 + GU @ 60 degree
Solids by Weight -	20.0 % +/- 1%
Solids by Volume -	20.5% +/- 1%
V.O.C. -	108 g/l minus water
Weight per gallon-	8.42 lbs./Gal.
Specific Gravity-	1.01
Dry Time -	2-4 touch dry 16 hours through dry Note dry times will be extended at low temperatures and high humidity

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 250-300 square feet per gallon

Rough Wood: 150 – 200 square feet per gallon

Hardwoods: 300-400 square feet per gallon

Note: Coverage will vary with the porosity of the wood

Interior Stain Formula

Technical Data Sheet

March 2013

IS-Series

TR-Series

ST-Series

SS-Series

Application

Use a spray applicator, roller or nylon polyester brush, paint pad

Clean Up

With soap and mild detergent

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd

#130-6251 Graybar Rd, Richmond, BC V6W 1H3

Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244

Email: canadainfo@timberprocoatings.com

