



Log Yard Treatment

Technical Data Sheet

March 2013

Description

Timber Pro Yard Treatment is designed as a log treatment to reduce the unwanted discoloration caused by fungi and damage caused by the ultraviolet rays. Timber Pro Yard Treatment also helps reduce the checking associated with rapid moisture loss in the logs.

Where to Use

Timber Pro Yard Treatment is for use on fresh logs that are too green to coat.

- All log species

Features and Benefits

- Water-based formula
- Protects logs in one simple step
- Easy to apply
- Final finishing can be applied on top
- Low odor
- Easy clean-up

Color Range and Packaging

Color	Clear only
Package Size	5 US gallons

Properties

Viscosity -	15-17 secs Zahn #2
Gloss Level -	Flat
Solids Content by Weight -	9.36%
Solids Content by Volume -	8.99%
V.O.C. -	88.0 g/l minus water
Weight per Gallon -	8.4 lbs.
Specific Gravity -	1.008
Dry Time -	4 Hours touch dry 16 hours through dry

Log Yard Treatment

Technical Data Sheet

March 2013

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

250-350 square feet per gallon

Note: This will vary with the porosity of the wood

Application

Use a spray applicator, roller or nylon polyester brush

Clean Up

With soap and mild detergent

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd

#130-6251 Graybar Rd, Richmond, BC V6W 1H3

Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244

Email: canadainfo@timberprocoatings.com

